

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 1/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR HG 96 Komponente A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS07

Exclamation mark



GHS09

Environment

Signal word: Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 2/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

Hazard components for labelling:

reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight \leq 700;
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

hazard statements for health hazards

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Precautionary Statements Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Response

P302 + P352	IF ON SKIN: Wash with plenty of water/...
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 25068-38-6 EC No.: 500-033-5 REACH No.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight \leq 700 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 H315-H317-H319-H411	40 - < 45 %
CAS No.: 3101-60-8 EC No.: 221-453-2	p-tert-butylphenyl 1-(2,3-epoxy)propyl ether Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 H315-H317-H319-H411	10 - < 15 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

No special measures are necessary.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 3/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

After ingestion:

IF SWALLOWED: Immediately call a doctor. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, harmful

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Keep away from sources of ignition - No smoking. Ventilate affected area. To follow: SECTION 7: Handling and storage Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 4/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached.

Hints on storage assembly:

No special measures are necessary.

Storage class: 12 - non-combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

No data available

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6	12.3 mg/m ³	① DNEL worker ② inhalative, short-term, systemic, (acute)
reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6	8.3 mg/kg	① DNEL worker ② Acute - dermal, systemic effects

Substance name	PNEC Value	① PNEC type
reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6	0.006 mg/l	① PNEC aquatic, freshwater
reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6	0.0006 mg/l	① PNEC aquatic, marine water

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2



Page 5/9

EUROREPAIR HG 96 Komponente A

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: brown

Odour: characteristic

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	<i>not determined</i>			
Decomposition temperature	<i>not determined</i>			
Flash point	> 135 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	> 290 °C			
Upper/lower flammability or explosive limits	<i>not determined</i>			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	1.42 g/cm ³			
Bulk density	<i>not determined</i>			
Water solubility	<i>not determined</i>			
Partition coefficient: n-octanol/water	<i>not determined</i>			
Dynamic viscosity	16,300 mPa*s	23 °C		
Kinematic viscosity	<i>not determined</i>			

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 6/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon dioxide, Nitrogen oxides (NO_x), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700	LD₅₀ oral: 15,000 mg/kg (Rat) LD₅₀ dermal: 23,000 mg/kg (Rabbit)

Skin corrosion/irritation:

May cause an allergic skin reaction. Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700	LC₅₀: 3.6 mg/l 4 d (fish, <i>Leuciscus idus</i> (golden orfe)) ErC₅₀: 220 mg/l 3 d (Algae/water plant) EC₅₀: 2.8 mg/l 2 d (crustaceans)

Assessment/classification:

Toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700	—

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 7/9

EUROTEAM
construction chemicals



EUROPAIR HG 96 Komponente A

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

08 02 99 Wastes not otherwise specified

Waste treatment options









Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700)
14.3. Transport hazard class(es)			
 9	 9	 9	 9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
		 MARINE POLLUTANT	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2

Page 8/9

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente A

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.6. Special precautions for user			
Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 90 Classification code: M6 tunnel restriction code: (-) Remark:	Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: M6 Remark:	Special provisions: 274 335 969 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-F Remark:	Special provisions: A97 A158 A197 Excepted Quantities (EQ): E1 Remark:

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

 [DE] National regulations

Water hazard class (WGK)

WGK:

2 - deutlich wassergefährdend

Description:

Documentation of self-classification carried out according to VwVwS, 3a.

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 3.2



Page 9/9

EUROREPAIR HG 96 Komponente A

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 1/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR HG 96 Komponente B_langsam

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 2/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05
Corrosion



GHS07
Exclamation mark

Signal word: Danger

Hazard components for labelling:

Phenol, 4-nonyl-, branched; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 1,3-Benzenedimethanamine; benzyl alcohol

hazard statements for health hazards

H302 + H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Hazard statements for environmental hazards

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 100-51-6 EC No.: 202-859-9 REACH No.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4 ⚠ Warning H302-H332	50 - < 55 %
CAS No.: 2855-13-2 EC No.: 220-666-8 REACH No.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 ⚠ ⚠ Danger H302-H312-H314-H317-H412	20 - < 25 %
CAS No.: 1477-55-0 EC No.: 216-032-5 REACH No.: 01-2119480150-50-XXXX	1,3-Benzenedimethanamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 H302-H314-H317-H332-H412	20 - < 25 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 3/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 84852-15-3 EC No.: 284-325-5	Phenol, 4-nonyl-, branched Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Corr. 1B  Danger H302-H314-H361fd-H410	1 - < 5 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Take off immediately all contaminated clothing.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use personal protection equipment.

6.1.2. For emergency responders

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 4/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing. Provide adequate ventilation.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached. Provide for retaining containers, eg. floor pan without outflow.

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 8A - Combustible corrosive substances

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	benzyl alcohol CAS No.: 100-51-6	① 5 ppm (22 mg/m ³) ② 10 ppm ③ 44 ppm ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 5/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
1,3-Benzenedimethanamine CAS No.: 1477-55-0	1.2 mg/m ³	① DNEL worker ② inhalative, short-term, local, (acute)
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.33 mg/kg	① DNEL worker ② dermal, short-term, local, (acute)

Substance name	PNEC Value	① PNEC type
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.06 mg/l	① PNEC aquatic, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.006 mg/l	① PNEC aquatic, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	3.18 mg/l	① PNEC sewage treatment plant
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	5.784 mg/kg	① PNEC sediment, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.578 mg/kg	① PNEC sediment, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	1.121 mg/kg	① PNEC soil
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.23 mg/l	① PNEC aquatic, intermittent release
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.094 mg/l	① PNEC aquatic, freshwater
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.0094 mg/l	① PNEC aquatic, marine water

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 6/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: yellow

Odour: Amines

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	> 200 °C			
Decomposition temperature	<i>not determined</i>			
Flash point	> 100 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	380 °C			
Upper/lower flammability or explosive limits	1.2 - 13 Vol-%			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	1.05 g/cm ³	23 °C		
Bulk density	<i>not determined</i>			
Water solubility	<i>not determined</i>			
Partition coefficient: n-octanol/water	<i>not determined</i>			
Dynamic viscosity	400 mPa*s			
Kinematic viscosity	<i>not determined</i>			

9.2. Other information

Solubility in different media: Solvent: Immiscible

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions. (SECTION 7: Handling and storage)

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Acid, Alkali (lye), Oxidising agent

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: Gases/vapours, toxic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 7/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LD₅₀ oral: 1,230 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (gas): 4,178 ppmV 4 h (Rat)
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LD₅₀ oral: 1,030 mg/kg (Rat) OECD 401 LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402 LC₅₀ Acute inhalation toxicity (vapour): >5.01 mg/l 4 h (Rat) OECD 403
1477-55-0	1,3-Benzenedimethanamine	LD₅₀ oral: 930 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit)
84852-15-3	Phenol, 4-nonyl-, branched	LD₅₀ oral: 1,300 mg/kg (Rat)

Skin corrosion/irritation:

Causes severe burns. May produce an allergic reaction.

Serious eye damage/irritation:

Causes serious eye damage.

Additional information:

The product has not been tested. The statement is derived from the properties of the single components.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 8/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LC₅₀: 460 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) EC₅₀: 400 mg/l (crustaceans, Daphnia magna (Big water flea)) EC₅₀: 640 mg/l 4 d (Algae/water plant, Scenedes mus subspicatus) LC₅₀: 27 mg/l 4 d (fish, Lepomis macrochirus (Bluegill))
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LC₅₀: 110 mg/l 4 d (fish, Leuciscus idus (golden orfe)) EC₅₀: 23 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >50 mg/l 3 d (Algae/water plant) NOEC: 3 mg/l 21 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 NOEC: 1.5 mg/l 3 d (Algae/water plant)
1477-55-0	1,3-Benzenedimethanamine	EC₅₀: 15.2 mg/l 2 d (crustaceans, Daphnia pulex (water flea)) OECD 202 EC₅₀: 20.3 mg/l 3 d (Algae/water plant, Selenast rum capricornutum) LC₅₀: 87.6 mg/l 4 d (fish, Oryzias latipes (Ricefish)) LC₅₀: >100 mg/l 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) LC₅₀: >100 mg/l 4 d (fish, Brachydanio rerio (zebra-fish))
84852-15-3	Phenol, 4-nonyl-, branched	LC₅₀: 0.137 mg/l 4 d (fish) ErC₅₀: 0.33 mg/l (Algae/water plant) EC₅₀: 0.13 mg/l 2 d (crustaceans)

Assessment/classification:

Harmful to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 9/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	Remark
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Yes, slowly	
1477-55-0	1,3-Benzenedimethanamine	Yes, slowly	Biodegradation: 22 %, Test duration: 28 d, Method: OECD 302 C, Biodegradation: 49 %, Test duration: 28 d, Method: OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C

12.3. Bioaccumulative potential

CAS No.	Substance name	Log K _{OW}	Bioconcentration factor (BCF)
100-51-6	benzyl alcohol	1.05	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	
1477-55-0	1,3-Benzenedimethanamine	0.18	3 Species: Cyprinus carpio (Common Carp)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
100-51-6	benzyl alcohol	—
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	—
1477-55-0	1,3-Benzenedimethanamine	—
84852-15-3	Phenol, 4-nonyl-, branched	—

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

08 02 99	Wastes not otherwise specified
----------	--------------------------------

Waste treatment options

Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name			
AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 10/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
--------------------------	-----------------------------	----------------------	------------------------------------

14.3. Transport hazard class(es)

 8	 8	 8	 8
--	--	--	--

14.4. Packing group

III	III	III	III
-----	-----	-----	-----

14.5. Environmental hazards

No	No	No	No
----	----	----	----

14.6. Special precautions for user

Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 80 Classification code: C7 tunnel restriction code: (E) Remark:	Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: C7 Remark:	Special provisions: 223 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-B Remark:	Special provisions: A3 Excepted Quantities (EQ): E1 Remark:
---	--	---	---

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Phenol, 4-nonyl-, branched. This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

15.1.2. National regulations

[DE] National regulations

Water hazard class (WGK)

WGK:

2 - deutlich wassergefährdend

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 11/11

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_langsam

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 1/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR HG 96 Komponente B_normal

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 2/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05
Corrosion



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

Hazard components for labelling:

Phenol, styrenated; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 1,3-Benzenedimethanamine; 2-piperazin-1-ylethylamine

hazard statements for health hazards

H302 + H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Precautionary Statements Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 100-51-6 EC No.: 202-859-9 REACH No.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4 ⚠ Warning H302-H332	35 - < 40 %
CAS No.: 61788-44-1 EC No.: 262-975-0 REACH No.: 01-2119980970-27-XXXX	Phenol, styrenated Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1 ⚠ ⚠ H315-H317-H411	20 - < 25 %
CAS No.: 2855-13-2 EC No.: 220-666-8 REACH No.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 ⚠ ⚠ Danger H302-H312-H314-H317-H412	15 - < 20 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 3/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 1477-55-0 EC No.: 216-032-5 REACH No.: 01-2119480150-50-XXXX	1,3-Benzenedimethanamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 H302-H314-H317-H332-H412	15 - < 20 %
CAS No.: 140-31-8 EC No.: 205-411-0 REACH No.: 01-2119471486-30-XXXX	2-piperazin-1-ylethylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 Danger H302-H312-H314-H317-H412	5 - < 10 %
CAS No.: 84852-15-3 EC No.: 284-325-5	Phenol, 4-nonyl-, branched Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Corr. 1B Danger H302-H314-H361fd-H410	1 - < 5 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Take off immediately all contaminated clothing.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of: Gases/vapours, toxic

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, harmful

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 4/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use personal protection equipment.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing. Provide adequate ventilation.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached. Provide for retaining containers, eg. floor pan without outflow.

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 8A - Combustible corrosive substances

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 5/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	benzyl alcohol CAS No.: 100-51-6	① 5 ppm (22 mg/m ³) ② 10 ppm ③ 44 ppm ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
1,3-Benzenedimethanamine CAS No.: 1477-55-0	1.2 mg/m ³	① DNEL worker ② inhalative, short-term, local, (acute)
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.33 mg/kg	① DNEL worker ② dermal, short-term, local, (acute)
2-piperazin-1-ylethylamine CAS No.: 140-31-8	21.4 mg/m ³	① DNEL worker ② inhalative, short-term, systemic, (acute)
2-piperazin-1-ylethylamine CAS No.: 140-31-8	20 mg/kg	① DNEL worker ② Acute - dermal, systemic effects

Substance name	PNEC Value	① PNEC type
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.06 mg/l	① PNEC aquatic, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.006 mg/l	① PNEC aquatic, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	3.18 mg/l	① PNEC sewage treatment plant
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	5.784 mg/kg	① PNEC sediment, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.578 mg/kg	① PNEC sediment, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	1.121 mg/kg	① PNEC soil
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.23 mg/l	① PNEC aquatic, intermittent release
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.094 mg/l	① PNEC aquatic, freshwater
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.0094 mg/l	① PNEC aquatic, marine water
2-piperazin-1-ylethylamine CAS No.: 140-31-8	0.058 mg/l	① PNEC aquatic, freshwater
2-piperazin-1-ylethylamine CAS No.: 140-31-8	0.0058 mg/l	① PNEC aquatic, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 6/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: yellow

Odour: Amines

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	> 220 °C			
Decomposition temperature	<i>not determined</i>			
Flash point	> 100 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	315 °C			
Upper/lower flammability or explosive limits	1 - 10.5 Vol-%			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	1 g/cm ³			
Bulk density	<i>not determined</i>			
Water solubility	<i>not determined</i>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 7/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

parameter		at °C	Method	Remark
Partition coefficient: n-octanol/ water	<i>not determined</i>			
Dynamic viscosity	475 mPa*s			
Kinematic viscosity	<i>not determined</i>			

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions. (SECTION 7: Handling and storage)

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Acid, Alkali (lye), Oxidising agent

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LD₅₀ oral: 1,230 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (gas): 4,178 ppmV 4 h (Rat)
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LD₅₀ oral: 1,030 mg/kg (Rat) OECD 401 LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402 LC₅₀ Acute inhalation toxicity (vapour): >5.01 mg/l 4 h (Rat) OECD 403
1477-55-0	1,3-Benzenedimethanamine	LD₅₀ oral: 930 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit)
140-31-8	2-piperazin-1-ylethylamine	LD₅₀ oral: 2,110 mg/kg (Rat) LD₅₀ dermal: 867 mg/kg (Rabbit)
84852-15-3	Phenol, 4-nonyl-, branched	LD₅₀ oral: 1,300 mg/kg (Rat)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 8/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

CAS No.	Substance name	Toxicological information
61788-44-1	Phenol, styrenated	LD₅₀ oral: >2,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat)

Skin corrosion/irritation:

Causes severe burns. May produce an allergic reaction.

Serious eye damage/irritation:

Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LC₅₀: 460 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) EC₅₀: 400 mg/l (crustaceans, Daphnia magna (Big water flea)) EC₅₀: 640 mg/l 4 d (Algae/water plant, Scenedesmus subspicatus) LC₅₀: 27 mg/l 4 d (fish, Lepomis macrochirus (Bluegill))
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LC₅₀: 110 mg/l 4 d (fish, Leuciscus idus (golden orfe)) EC₅₀: 23 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >50 mg/l 3 d (Algae/water plant) NOEC: 3 mg/l 21 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 NOEC: 1.5 mg/l 3 d (Algae/water plant)
1477-55-0	1,3-Benzenedimethanamine	EC₅₀: 15.2 mg/l 2 d (crustaceans, Daphnia pulex (water flea)) OECD 202 EC₅₀: 20.3 mg/l 3 d (Algae/water plant, Selenastrum capricornutum) LC₅₀: 87.6 mg/l 4 d (fish, Oryzias latipes (Ricefish)) LC₅₀: >100 mg/l 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) LC₅₀: >100 mg/l 4 d (fish, Brachydanio rerio (zebra-fish))
140-31-8	2-piperazin-1-ylethylamine	LC₅₀: 2,190 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) OECD 203 EC₅₀: 58 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >1,000 mg/l 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201 EC₅₀: 494 mg/l 2 d (Algae/water plant, Selenastrum capricornutum) LC₅₀: 368 mg/l 4 d (fish, Poecilia reticulata (Guppy))
84852-15-3	Phenol, 4-nonyl-, branched	LC₅₀: 0.137 mg/l 4 d (fish) ErC₅₀: 0.33 mg/l (Algae/water plant) EC₅₀: 0.13 mg/l 2 d (crustaceans)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 9/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

CAS No.	Substance name	Toxicological information
61788-44-1	Phenol, styrenated	LC₅₀: 14.8 mg/l 4 d (fish, Brachydanio rerio (zebra-fish)) OECD 203 EC₅₀: >1 - 10 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 EC₅₀: 3.14 mg/l 3 d (Algae/water plant, Scenedesmus subspicatus) OECD 201 NOEC: 1.9 mg/l 12 d (fish, Oryzias latipes (Ricefish)) NOEC: 0.2 mg/l 21 d (crustaceans, Daphnia magna (Big water flea))

Assessment/classification:

Toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	Remark
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Yes, slowly	
1477-55-0	1,3-Benzenedimethanamine	Yes, slowly	Biodegradation: 22 %, Test duration: 28 d, Method: OECD 302 C, Biodegradation: 49 %, Test duration: 28 d, Method: OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C
140-31-8	2-piperazin-1-ylethylamine	Yes, slowly	Biodegradation: 0 %, Test duration: 28 d, Method: OECD F
61788-44-1	Phenol, styrenated	Yes, slowly	Biodegradation: 4 %, Method: 310

12.3. Bioaccumulative potential

CAS No.	Substance name	Log K _{OW}	Bioconcentration factor (BCF)
100-51-6	benzyl alcohol	1.05	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	
1477-55-0	1,3-Benzenedimethanamine	0.18	3 Species: Cyprinus carpio (Common Carp)
140-31-8	2-piperazin-1-ylethylamine	-1.48	
61788-44-1	Phenol, styrenated	4	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
100-51-6	benzyl alcohol	—
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	—
1477-55-0	1,3-Benzenedimethanamine	—
140-31-8	2-piperazin-1-ylethylamine	—
84852-15-3	Phenol, 4-nonyl-, branched	—
61788-44-1	Phenol, styrenated	—

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 10/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

08 02 99 Wastes not otherwise specified

Waste treatment options








Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name			
AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol, N-aminoethylpiperazine)	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine, nonylphenol)
14.3. Transport hazard class(es)			
 8	 8	 8	 8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
		 MARINE POLLUTANT	No
14.6. Special precautions for user			
Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 80 Classification code: C7 tunnel restriction code: (E) Remark:	Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: C7 Remark:	Special provisions: 223 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-B Remark:	Special provisions: A3 Excepted Quantities (EQ): E1 Remark:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 11/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Phenol, 4-nonyl-, branched. This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

15.1.2. National regulations

[DE] National regulations

Water hazard class (WGK)

WGK:

3 - stark wassergefährdend

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.3

Page 12/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_normal

Hazard statements

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 1/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR HG 96 Komponente B_schnell

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 2/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05
Corrosion



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

Hazard components for labelling:

Phenol, styrenated; 2-piperazin-1-ylethylamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 1,3-Benzenedimethanamine

hazard statements for health hazards

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Precautionary Statements Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 61788-44-1 EC No.: 262-975-0 REACH No.: 01-2119980970-27-XXXX	Phenol, styrenated Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1 H315-H317-H411	50 - < 55 %
CAS No.: 100-51-6 EC No.: 202-859-9 REACH No.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4 Warning H302-H332	15 - < 20 %
CAS No.: 140-31-8 EC No.: 205-411-0 REACH No.: 01-2119471486-30-XXXX	2-piperazin-1-ylethylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 Danger H302-H312-H314-H317-H412	15 - < 20 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 3/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 2855-13-2 EC No.: 220-666-8 REACH No.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 Danger H302-H312-H314-H317-H412	1 - < 5 %
CAS No.: 1477-55-0 EC No.: 216-032-5 REACH No.: 01-2119480150-50-XXXX	1,3-Benzenedimethanamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 H302-H314-H317-H332-H412	1 - < 5 %
CAS No.: 84852-15-3 EC No.: 284-325-5	Phenol, 4-nonyl-, branched Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Corr. 1B Danger H302-H314-H361fd-H410	< 1 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Take off immediately all contaminated clothing.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of: Gases/vapours, toxic

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, harmful

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 4/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use personal protection equipment.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing. (See section 8.) Provide adequate ventilation.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached. Provide for retaining containers, eg. floor pan without outflow.

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 8A - Combustible corrosive substances

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 5/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	benzyl alcohol CAS No.: 100-51-6	① 5 ppm (22 mg/m ³) ② 10 ppm ③ 44 ppm ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
2-piperazin-1-ylethylamine CAS No.: 140-31-8	21.4 mg/m ³	① DNEL worker ② inhalative, short-term, systemic, (acute)
2-piperazin-1-ylethylamine CAS No.: 140-31-8	20 mg/kg	① DNEL worker ② Acute - dermal, systemic effects
1,3-Benzenedimethanamine CAS No.: 1477-55-0	1.2 mg/m ³	① DNEL worker ② inhalative, short-term, local, (acute)
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.33 mg/kg	① DNEL worker ② dermal, short-term, local, (acute)

Substance name	PNEC Value	① PNEC type
2-piperazin-1-ylethylamine CAS No.: 140-31-8	0.058 mg/l	① PNEC aquatic, freshwater
2-piperazin-1-ylethylamine CAS No.: 140-31-8	0.0058 mg/l	① PNEC aquatic, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.06 mg/l	① PNEC aquatic, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.006 mg/l	① PNEC aquatic, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	3.18 mg/l	① PNEC sewage treatment plant
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	5.784 mg/kg	① PNEC sediment, freshwater
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.578 mg/kg	① PNEC sediment, marine water
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	1.121 mg/kg	① PNEC soil
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2	0.23 mg/l	① PNEC aquatic, intermittent release
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.094 mg/l	① PNEC aquatic, freshwater
1,3-Benzenedimethanamine CAS No.: 1477-55-0	0.0094 mg/l	① PNEC aquatic, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 6/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: yellow

Odour: Amines

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	> 220 °C			
Decomposition temperature	<i>not determined</i>			
Flash point	> 100 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	315 °C			
Upper/lower flammability or explosive limits	1 - 10.5 Vol-%			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	0.97 g/cm ³			
Bulk density	<i>not determined</i>			
Water solubility	<i>not determined</i>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 7/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

parameter		at °C	Method	Remark
Partition coefficient: n-octanol/ water	<i>not determined</i>			
Dynamic viscosity	550 mPa*s			
Kinematic viscosity	<i>not determined</i>			

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions. (SECTION 7: Handling and storage)

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Acid, Alkali (lye), Oxidising agent

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LD₅₀ oral: 1,230 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (gas): 4,178 ppmV 4 h (Rat)
140-31-8	2-piperazin-1-ylethylamine	LD₅₀ oral: 2,110 mg/kg (Rat) LD₅₀ dermal: 867 mg/kg (Rabbit)
61788-44-1	Phenol, styrenated	LD₅₀ oral: >2,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat)
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LD₅₀ oral: 1,030 mg/kg (Rat) OECD 401 LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402 LC₅₀ Acute inhalation toxicity (vapour): >5.01 mg/l 4 h (Rat) OECD 403
1477-55-0	1,3-Benzenedimethanamine	LD₅₀ oral: 930 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 8/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

CAS No.	Substance name	Toxicological information
84852-15-3	Phenol, 4-nonyl-, branched	LD₅₀ oral: 1,300 mg/kg (Rat)

Skin corrosion/irritation:

Causes severe burns. May produce an allergic reaction.

Serious eye damage/irritation:

Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
100-51-6	benzyl alcohol	LC₅₀: 460 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) EC₅₀: 400 mg/l (crustaceans, Daphnia magna (Big water flea)) EC₅₀: 640 mg/l 4 d (Algae/water plant, Scenedesmus subspicatus) LC₅₀: 27 mg/l 4 d (fish, Lepomis macrochirus (Bluegill))
140-31-8	2-piperazin-1-ylethylamine	LC₅₀: 2,190 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) OECD 203 EC₅₀: 58 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >1,000 mg/l 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201 EC₅₀: 494 mg/l 2 d (Algae/water plant, Selenastrum capricornutum) LC₅₀: 368 mg/l 4 d (fish, Poecilia reticulata (Guppy))
61788-44-1	Phenol, styrenated	LC₅₀: 14.8 mg/l 4 d (fish, Brachydanio rerio (zebra-fish)) OECD 203 EC₅₀: >1 - 10 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 EC₅₀: 3.14 mg/l 3 d (Algae/water plant, Scenedesmus subspicatus) OECD 201 NOEC: 1.9 mg/l 12 d (fish, Oryzias latipes (Ricefish)) NOEC: 0.2 mg/l 21 d (crustaceans, Daphnia magna (Big water flea))
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	LC₅₀: 110 mg/l 4 d (fish, Leuciscus idus (golden orfe)) EC₅₀: 23 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >50 mg/l 3 d (Algae/water plant) NOEC: 3 mg/l 21 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 NOEC: 1.5 mg/l 3 d (Algae/water plant)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 9/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

CAS No.	Substance name	Toxicological information
1477-55-0	1,3-Benzenedimethanamine	EC₅₀ : 15.2 mg/l 2 d (crustaceans, Daphnia pulex (water flea)) OECD 202 EC₅₀ : 20.3 mg/l 3 d (Algae/water plant, Selenast rum capricornutum) LC₅₀ : 87.6 mg/l 4 d (fish, Oryzias latipes (Ricefish)) LC₅₀ : >100 mg/l 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) LC₅₀ : >100 mg/l 4 d (fish, Brachydanio rerio (zebra-fish))
84852-15-3	Phenol, 4-nonyl-, branched	LC₅₀ : 0.137 mg/l 4 d (fish) ErC₅₀ : 0.33 mg/l (Algae/water plant) EC₅₀ : 0.13 mg/l 2 d (crustaceans)

Assessment/classification:

Toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	Remark
140-31-8	2-piperazin-1-ylethylamine	Yes, slowly	Biodegradation: 0 %, Test duration: 28 d, Method: OECD F
61788-44-1	Phenol, styrenated	Yes, slowly	Biodegradation: 4 %, Method: 310
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Yes, slowly	
1477-55-0	1,3-Benzenedimethanamine	Yes, slowly	Biodegradation: 22 %, Test duration: 28 d, Method: OECD 302 C, Biodegradation: 49 %, Test duration: 28 d, Method: OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C

12.3. Bioaccumulative potential

CAS No.	Substance name	Log K _{ow}	Bioconcentration factor (BCF)
100-51-6	benzyl alcohol	1.05	
140-31-8	2-piperazin-1-ylethylamine	-1.48	
61788-44-1	Phenol, styrenated	4	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	
1477-55-0	1,3-Benzenedimethanamine	0.18	3 Species: Cyprinus carpio (Common Carp)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
100-51-6	benzyl alcohol	—
140-31-8	2-piperazin-1-ylethylamine	—
61788-44-1	Phenol, styrenated	—
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	—
1477-55-0	1,3-Benzenedimethanamine	—
84852-15-3	Phenol, 4-nonyl-, branched	—

12.6. Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 10/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

08 02 99	Wastes not otherwise specified
----------	--------------------------------

Waste treatment options








Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name			
AMINES, LIQUID, CORROSIVE, N.O.S. (N-aminoethylpiperazine)	AMINES, LIQUID, CORROSIVE, N.O.S. (N-aminoethylpiperazine)	AMINES, LIQUID, CORROSIVE, N.O.S. (N-aminoethylpiperazine)	AMINES, LIQUID, CORROSIVE, N.O.S. (N-aminoethylpiperazine)
14.3. Transport hazard class(es)			
 8	 8	 8	 8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
		 MARINE POLLUTANT	No

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 11/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

Land transport (ADR/ RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)
14.6. Special precautions for user			
Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 80 Classification code: C7 tunnel restriction code: (E) Remark:	Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: C7 Remark:	Special provisions: 223 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-B Remark:	Special provisions: A3 Excepted Quantities (EQ): E1 Remark:

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Phenol, 4-nonyl-, branched. This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

15.1.2. National regulations

 **[DE] National regulations**

Water hazard class (WGK)

WGK:

3 - stark wassergefährdend

Description:

Documentation of self-classification carried out according to VwVwS, 3a.

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 10 Mar 2020

Version: 2.0

Page 12/12

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_schnell

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 1/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR HG 96 Komponente B_superschnell

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Hazardous to the aquatic environment (<i>Aquatic Acute 1</i>)	H400: Very toxic to aquatic life.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>)	H410: Very toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS07

Exclamation mark



GHS09

Environment

Signal word: Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 2/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

Hazard components for labelling:

pentaerythritol tetrakis(3-mercaptopropionate); 3-mercaptopropionic acid

hazard statements for health hazards

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.

Hazard statements for environmental hazards

H410	Very toxic to aquatic life with long lasting effects.
------	---

Precautionary Statements Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Response

P302 + P352	IF ON SKIN: Wash with plenty of water/....
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 7575-23-7 EC No.: 231-472-8	pentaerythritol tetrakis(3-mercaptopropionate) Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Skin Sens. 1 H302-H317-H400-H410 M-factor (acute): 1	95 - ≤ 100 %
CAS No.: 107-96-0 EC No.: 203-537-0	3-mercaptopropionic acid Acute Tox. 3, Acute Tox. 4, Met. Corr. 1, Skin Corr. 1A H290-H301-H314-H332	< 1 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Take off immediately all contaminated clothing.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

Induce vomiting when the affected person is not unconscious. Rinse mouth immediately and drink plenty of water. Call a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 3/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit. If decomposition products are inhaled the following symptoms can occur: Harmful

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use personal protection equipment.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing. (See section 8.) Provide adequate ventilation.

Fire prevent measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached. Provide for retaining containers, eg. floor pan without outflow.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 4/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: colourless

Odour: characteristic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

EUROTEAM
construction chemicals



Page 5/8

EUROREPAIR HG 96 Komponente B_superschnell

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	-40.1 °C			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	520 °C			
Decomposition temperature	<i>not determined</i>			
Flash point	214 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	300 - 400 °C			
Upper/lower flammability or explosive limits	<i>not determined</i>			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	1.27 - 1.28 g/cm ³	20 °C		
Bulk density	<i>not determined</i>			
Water solubility	3.69 g/l	20 °C		
Partition coefficient: n-octanol/water	<i>not determined</i>			
Dynamic viscosity	<i>not determined</i>			
Kinematic viscosity	<i>not determined</i>			

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions. (SECTION 7: Handling and storage)

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: Gases/vapours, toxic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 6/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
7575-23-7	pentaerythritol tetrakis(3-mercaptopropionate)	LD₅₀ oral: 1,000 – 2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (vapour): 20 mg/l (Rat)
107-96-0	3-mercaptopropionic acid	LD₅₀ oral: 96 mg/kg (Rat) ATE inhalativ Gase: 1.5 ppmV ATE inhalativ Dämpfe: 11 mg/l

Acute inhalation toxicity:

Harmful if swallowed or if inhaled.

Skin corrosion/irritation:

May cause an allergic skin reaction.

Additional information:

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
7575-23-7	pentaerythritol tetrakis(3-mercaptopropionate)	LC₅₀: 0.42 mg/l 4 d (fish, <i>Oncorhynchus mykiss</i> (Rainbow trout)) EC₅₀: 0.71 mg/l 2 d (crustaceans, <i>Daphnia magna</i> (Big water flea))

Assessment/classification:

Very toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
7575-23-7	pentaerythritol tetrakis(3-mercaptopropionate)	—
107-96-0	3-mercaptopropionic acid	—

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 7/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

Waste code product:

16 05 08 * | discarded organic chemicals consisting of or containing hazardous substances

*: Evidence for disposal must be provided.

Waste treatment options









Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pentaerythritol tetrakis(3-mercaptopropionate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pentaerythritol tetrakis(3-mercaptopropionate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pentaerythritol tetrakis(3-mercaptopropionate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pentaerythritol tetrakis(3-mercaptopropionate))
14.3. Transport hazard class(es)			
 9	 9	 9	 9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
		 MARINE POLLUTANT	
14.6. Special precautions for user			
Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 90 Classification code: M6 tunnel restriction code: (-) Remark:	Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: M6 Remark:	Special provisions: 274 335 969 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-F Remark:	Special provisions: A97 A158 A197 Excepted Quantities (EQ): E1 Remark:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2020

Print date: 11 Mar 2020

Version: 2.0

Page 8/8

EUROTEAM
construction chemicals



EUROREPAIR HG 96 Komponente B_superschnell

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

[DE] National regulations

Water hazard class (WGK)

WGK:

3 - stark wassergefährdend

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Hazardous to the aquatic environment (<i>Aquatic Acute 1</i>)	H400: Very toxic to aquatic life.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>)	H410: Very toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available