

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 1/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR PC 96 WHG Komponente A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Skin corrosion/irritation (<i>Skin Irrit. 2</i>) | H315: Causes skin irritation. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>) | H412: Harmful to aquatic life with long lasting effects. | |

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS07

Exclamation mark

Signal word: Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 2/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

Hazard components for labelling:

reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight ≤ 700 ;
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

hazard statements for health hazards

| | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

Hazard statements for environmental hazards

| | |
|------|--|
| H412 | Harmful to aquatic life with long lasting effects. |
|------|--|

Precautionary Statements Prevention

| | |
|------|--|
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

Precautionary Statements Response

| | |
|-------------|--|
| P302 + P352 | IF ON SKIN: Wash with plenty of water/... |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

| product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|--|---------------|
| CAS No.: 25068-38-6 EC No.: 500-033-5 REACH No.: 01-2119456619-26-XXXX | reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight ≤ 700 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 H315-H317-H319-H411 | 1 - < 5 % |
| CAS No.: 3101-60-8 EC No.: 221-453-2 | p-tert-butylphenyl 1-(2,3-epoxy)propyl ether Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 H315-H317-H319-H411 | 1 - < 5 % |

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

IF SWALLOWED: Immediately call a doctor. Keep at rest. Do NOT induce vomiting.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 3/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Keep away from sources of ignition - No smoking. Ventilate affected area. To follow: SECTION 7: Handling and storage Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Put lids on containers immediately after use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 4/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

Hints on storage assembly:

Do not store together with: Oxidising agent, Food and feedingstuffs, Acid, alkaline Substances

Storage class: 13 - Non-combustible solids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. storage temperature: 15 °C - 20°C .

Protect against: Frost.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

No data available

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

| Substance name | DNEL value | ① DNEL type ② Exposure route |
|---|------------------------|--|
| reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6 | 12.3 mg/m ³ | ① DNEL worker ② inhalative, short-term, systemic, (acute) |
| reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6 | 8.3 mg/kg | ① DNEL worker ② Acute - dermal, systemic effects |

| Substance name | PNEC Value | ① PNEC type |
|---|-------------|------------------------------|
| reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6 | 0.006 mg/l | ① PNEC aquatic, freshwater |
| reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 CAS No.: 25068-38-6 | 0.0006 mg/l | ① PNEC aquatic, marine water |

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. Wear suitable protective clothing and gloves.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

EUROTEAM
construction chemicals



Page 5/8

EUROREPAIR PC 96 WHG Komponente A

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: solid

Colour: grey

Odour: characteristic

Safety relevant basis data

| parameter | | at °C | Method | Remark |
|--|------------------------|-------|--------|--------|
| pH | <i>not determined</i> | | | |
| Melting point | <i>not determined</i> | | | |
| Freezing point | <i>not determined</i> | | | |
| Initial boiling point and boiling range | 2,230 °C | | | |
| Decomposition temperature | <i>not determined</i> | | | |
| Flash point | <i>not determined</i> | | | |
| Evaporation rate | <i>not determined</i> | | | |
| Auto-ignition temperature | <i>not determined</i> | | | |
| Upper/lower flammability or explosive limits | <i>not determined</i> | | | |
| Vapour pressure | <i>not determined</i> | | | |
| Vapour density | <i>not determined</i> | | | |
| Density | 2.14 g/cm ³ | 20 °C | | |
| Bulk density | <i>not determined</i> | | | |
| Water solubility | <i>not determined</i> | | | |
| Partition coefficient: n-octanol/water | <i>not determined</i> | | | |
| Dynamic viscosity | <i>not determined</i> | | | |
| Kinematic viscosity | <i>not determined</i> | | | |

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 6/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

10.5. Incompatible materials

Do not store together with: Oxidising substances, Acids, Heavy metals

10.6. Hazardous decomposition products

Carbon dioxide, Nitrogen oxides (NO_x), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| CAS No. | Substance name | Toxicological information |
|------------|---|---|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 | LD₅₀ oral: 15,000 mg/kg (Rat) LD₅₀ dermal: 23,000 mg/kg (Rabbit) |

Skin corrosion/irritation:

May cause an allergic skin reaction.

Serious eye damage/irritation:

Processing vapours can irritate the respiratory tracts, skin and eyes.

Respiratory or skin sensitisation:

May cause sensitization by inhalation and skin contact.

Additional information:

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

| CAS No. | Substance name | Toxicological information |
|------------|---|---|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 | LC₅₀: 3.6 mg/l 4 d (fish, <i>Leuciscus idus</i> (golden orfe)) ErC₅₀: 220 mg/l 3 d (Algae/water plant) EC₅₀: 2.8 mg/l 2 d (crustaceans) |

Assessment/classification:

Harmful to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

| CAS No. | Substance name | Results of PBT and vPvB assessment |
|------------|---|------------------------------------|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin)epoxy resin (number average) molecular weight <= 700 | — |

12.6. Other adverse effects

The product has not been tested. The statement is derived from the properties of the single components.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 7/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

| | |
|----------|--------------------------------|
| 08 02 99 | Wastes not otherwise specified |
|----------|--------------------------------|

Waste treatment options

Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

No dangerous good in sense of these transport regulations.

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|--|--|--|--|
| 14.1. UN-No. | | | |
| No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. |
| 14.2. UN proper shipping name | | | |
| No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. | No dangerous good in sense of these transport regulations. |
| 14.3. Transport hazard class(es) | | | |
| not relevant | | | |
| 14.4. Packing group | | | |
| not relevant | | | |
| 14.5. Environmental hazards | | | |
| not relevant | | | |
| 14.6. Special precautions for user | | | |
| not relevant | | | |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

 [DE] National regulations

Water hazard class (WGK)

WGK:

2 - deutlich wassergefährdend

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 8/8

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente A

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Skin corrosion/irritation (<i>Skin Irrit. 2</i>) | H315: Causes skin irritation. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>) | H412: Harmful to aquatic life with long lasting effects. | |

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

| Hazard statements | |
|-------------------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

16.6. Training advice

No data available

16.7. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 1/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROREPAIR PC 96 WHG Komponente B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Acute toxicity (oral) (<i>Acute Tox. 4</i>) | H302: Harmful if swallowed. | |
| Skin corrosion/irritation (<i>Skin Corr. 1B</i>) | H314: Causes severe skin burns and eye damage. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Dam. 1</i>) | H318: Causes serious eye damage. | |
| Acute toxicity (inhalative) (<i>Acute Tox. 4</i>) | H332: Harmful if inhaled. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>) | H411: Toxic to aquatic life with long lasting effects. | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 2/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05
Corrosion



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

Hazard components for labelling:

Phenol, styrenated; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 1,3-Benzenedimethanamine; 2-piperazin-1-ylethylamine

hazard statements for health hazards

| | |
|-------------|--|
| H302 + H332 | Harmful if swallowed or if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |

Hazard statements for environmental hazards

| | |
|------|--|
| H411 | Toxic to aquatic life with long lasting effects. |
|------|--|

Precautionary Statements Prevention

| | |
|------|--|
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

Precautionary Statements Response

| | |
|--------------------|--|
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTER/doctor/... if you feel unwell. |

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

| product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|---|----------------|
| CAS No.: 100-51-6 EC No.: 202-859-9 REACH No.: 01-2119492630-38-XXXX | benzyl alcohol Acute Tox. 4 ⚠ Warning H302-H332 | 30 - < 35 % |
| CAS No.: 61788-44-1 EC No.: 262-975-0 REACH No.: 01-2119980970-27-XXXX | Phenol, styrenated Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1 ⚠ ⚠ H315-H317-H411 | 25 - < 30 % |
| CAS No.: 2855-13-2 EC No.: 220-666-8 REACH No.: 01-2119514687-32-XXXX | 3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 ⚠ ⚠ Danger H302-H312-H314-H317-H412 | 15 - < 20 % |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 3/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

| product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|---|----------------|
| CAS No.: 1477-55-0 EC No.: 216-032-5 REACH No.: 01-2119480150-50-XXXX | 1,3-Benzenedimethanamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 H302-H314-H317-H332-H412 | 15 - < 20 % |
| CAS No.: 140-31-8 EC No.: 205-411-0 REACH No.: 01-2119471486-30-XXXX | 2-piperazin-1-ylethylamine Acute Tox. 4, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 Danger H302-H312-H314-H317-H412 | 5 - < 10 % |
| CAS No.: 84852-15-3 EC No.: 284-325-5 | Phenol, 4-nonyl-, branched Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Corr. 1B Danger H302-H314-H361fd-H410 | 1 - < 5 % |

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Take off immediately all contaminated clothing.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of: Gases/vapours, toxic

Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, harmful

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 4/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use personal protection equipment.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clear contaminated areas thoroughly. (Water (with cleaning agent)). Unsuitable material: Solvent

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Avoid: Eye contact, Skin contact. When using do not eat, drink or smoke. Wear suitable protective clothing. Provide adequate ventilation.

Fire prevent measures:

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Packaging materials:

Keep only in the original container in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed. Never use pressure to empty container. Put lids on containers immediately after use. Store detached. Provide for retaining containers, eg. floor pan without outflow.

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 8A - Combustible corrosive substances

Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store in a cool dry place. storage temperature: 15 °C - 30°C . Notice the directions for use on the label. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

Recommendation:

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 5/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

| Limit value type (country of origin) | Substance name | ① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark |
|--------------------------------------|-------------------------------------|--|
| TRGS 900 (DE) | benzyl alcohol CAS No.: 100-51-6 | ① 5 ppm (22 mg/m ³) ② 10 ppm ③ 44 ppm ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) |

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

| Substance name | DNEL value | ① DNEL type ② Exposure route |
|---|------------------------|--|
| 1,3-Benzenedimethanamine CAS No.: 1477-55-0 | 1.2 mg/m ³ | ① DNEL worker ② inhalative, short-term, local, (acute) |
| 1,3-Benzenedimethanamine CAS No.: 1477-55-0 | 0.33 mg/kg | ① DNEL worker ② dermal, short-term, local, (acute) |
| 2-piperazin-1-ylethylamine CAS No.: 140-31-8 | 21.4 mg/m ³ | ① DNEL worker ② inhalative, short-term, systemic, (acute) |
| 2-piperazin-1-ylethylamine CAS No.: 140-31-8 | 20 mg/kg | ① DNEL worker ② Acute - dermal, systemic effects |

| Substance name | PNEC Value | ① PNEC type |
|--|-------------|--------------------------------------|
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 0.06 mg/l | ① PNEC aquatic, freshwater |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 0.006 mg/l | ① PNEC aquatic, marine water |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 3.18 mg/l | ① PNEC sewage treatment plant |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 5.784 mg/kg | ① PNEC sediment, freshwater |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 0.578 mg/kg | ① PNEC sediment, marine water |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 1.121 mg/kg | ① PNEC soil |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 | 0.23 mg/l | ① PNEC aquatic, intermittent release |
| 1,3-Benzenedimethanamine CAS No.: 1477-55-0 | 0.094 mg/l | ① PNEC aquatic, freshwater |
| 1,3-Benzenedimethanamine CAS No.: 1477-55-0 | 0.0094 mg/l | ① PNEC aquatic, marine water |
| 2-piperazin-1-ylethylamine CAS No.: 140-31-8 | 0.058 mg/l | ① PNEC aquatic, freshwater |
| 2-piperazin-1-ylethylamine CAS No.: 140-31-8 | 0.0058 mg/l | ① PNEC aquatic, marine water |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 6/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. By long-term hand contact: Use protective skin cream before handling the product. Suitable gloves type: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride). Thickness of the glove material: > 5 mm. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable protective clothing and gloves. After contact with skin, wash immediately with plenty of water.

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. Suitable respiratory protection apparatus: Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Avoid: Skin contact, Eye contact.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: yellow

Odour: Amines

Safety relevant basis data

| parameter | | at °C | Method | Remark |
|--|-----------------------|-------|--------|--------|
| pH | <i>not determined</i> | | | |
| Melting point | <i>not determined</i> | | | |
| Freezing point | <i>not determined</i> | | | |
| Initial boiling point and boiling range | > 220 °C | | | |
| Decomposition temperature | <i>not determined</i> | | | |
| Flash point | > 100 °C | | | |
| Evaporation rate | <i>not determined</i> | | | |
| Auto-ignition temperature | 315 °C | | | |
| Upper/lower flammability or explosive limits | 1 - 10.5 Vol-% | | | |
| Vapour pressure | <i>not determined</i> | | | |
| Vapour density | <i>not determined</i> | | | |
| Density | 1 g/cm ³ | | | |
| Bulk density | <i>not determined</i> | | | |
| Water solubility | <i>not determined</i> | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 7/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

| parameter | | at °C | Method | Remark |
|--|-----------------------|-------|--------|--------|
| Partition coefficient: n-octanol/ water | <i>not determined</i> | | | |
| Dynamic viscosity | 475 mPa*s | | | |
| Kinematic viscosity | <i>not determined</i> | | | |

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions. (SECTION 7: Handling and storage)

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Acid, Alkali (lye), Oxidising agent

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| CAS No. | Substance name | Toxicological information |
|------------|--|--|
| 100-51-6 | benzyl alcohol | LD₅₀ oral: 1,230 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (gas): 4,178 ppmV 4 h (Rat) |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | LD₅₀ oral: 1,030 mg/kg (Rat) OECD 401 LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402 LC₅₀ Acute inhalation toxicity (vapour): >5.01 mg/l 4 h (Rat) OECD 403 |
| 1477-55-0 | 1,3-Benzenedimethanamine | LD₅₀ oral: 930 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit) |
| 140-31-8 | 2-piperazin-1-ylethylamine | LD₅₀ oral: 2,110 mg/kg (Rat) LD₅₀ dermal: 867 mg/kg (Rabbit) |
| 84852-15-3 | Phenol, 4-nonyl-, branched | LD₅₀ oral: 1,300 mg/kg (Rat) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 8/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

| CAS No. | Substance name | Toxicological information |
|------------|--------------------|--|
| 61788-44-1 | Phenol, styrenated | LD₅₀ oral: >2,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat) |

Skin corrosion/irritation:

Causes severe burns. May produce an allergic reaction.

Serious eye damage/irritation:

Causes serious eye damage.

Additional information:

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

| CAS No. | Substance name | Toxicological information |
|-----------|--|---|
| 100-51-6 | benzyl alcohol | LC₅₀: 460 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) EC₅₀: 400 mg/l (crustaceans, Daphnia magna (Big water flea)) EC₅₀: 640 mg/l 4 d (Algae/water plant, Scenedesmus subspicatus) LC₅₀: 27 mg/l 4 d (fish, Lepomis macrochirus (Bluegill)) |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | LC₅₀: 110 mg/l 4 d (fish, Leuciscus idus (golden orfe)) EC₅₀: 23 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >50 mg/l 3 d (Algae/water plant) NOEC: 3 mg/l 21 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 NOEC: 1.5 mg/l 3 d (Algae/water plant) |
| 1477-55-0 | 1,3-Benzenedimethanamine | EC₅₀: 15.2 mg/l 2 d (crustaceans, Daphnia pulex (water flea)) OECD 202 EC₅₀: 20.3 mg/l 3 d (Algae/water plant, Selenastrum capricornutum) LC₅₀: 87.6 mg/l 4 d (fish, Oryzias latipes (Ricefish)) LC₅₀: >100 mg/l 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) LC₅₀: >100 mg/l 4 d (fish, Brachydanio rerio (zebra-fish)) |
| 140-31-8 | 2-piperazin-1-ylethylamine | LC₅₀: 2,190 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) OECD 203 EC₅₀: 58 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 ErC₅₀: >1,000 mg/l 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201 EC₅₀: 494 mg/l 2 d (Algae/water plant, Selenastrum capricornutum) LC₅₀: 368 mg/l 4 d (fish, Poecilia reticulata (Guppy)) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 9/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

| CAS No. | Substance name | Toxicological information |
|------------|----------------------------|---|
| 84852-15-3 | Phenol, 4-nonyl-, branched | LC₅₀ : 0.137 mg/l 4 d (fish) ErC₅₀ : 0.33 mg/l (Algae/water plant) EC₅₀ : 0.13 mg/l 2 d (crustaceans) |
| 61788-44-1 | Phenol, styrenated | LC₅₀ : 14.8 mg/l 4 d (fish, Brachydanio rerio (zebra-fish)) OECD 203 EC₅₀ : >1 – 10 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202 EC₅₀ : 3.14 mg/l 3 d (Algae/water plant, Scenedesmus subspicatus) OECD 201 NOEC : 1.9 mg/l 12 d (fish, Oryzias latipes (Ricefish)) NOEC : 0.2 mg/l 21 d (crustaceans, Daphnia magna (Big water flea)) |

Assessment/classification:

Toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil.

12.2. Persistence and degradability

| CAS No. | Substance name | Biodegradation | Remark |
|------------|--|----------------|---|
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | Yes, slowly | |
| 1477-55-0 | 1,3-Benzenedimethanamine | Yes, slowly | Biodegradation: 22 %, Test duration: 28 d, Method: OECD 302 C, Biodegradation: 49 %, Test duration: 28 d, Method: OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C |
| 140-31-8 | 2-piperazin-1-ylethylamine | Yes, slowly | Biodegradation: 0 %, Test duration: 28 d, Method: OECD F |
| 61788-44-1 | Phenol, styrenated | Yes, slowly | Biodegradation: 4 %, Method: 310 |

12.3. Bioaccumulative potential

| CAS No. | Substance name | Log K _{OW} | Bioconcentration factor (BCF) |
|------------|--|---------------------|--|
| 100-51-6 | benzyl alcohol | 1.05 | |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 0.99 | |
| 1477-55-0 | 1,3-Benzenedimethanamine | 0.18 | 3 Species: Cyprinus carpio (Common Carp) |
| 140-31-8 | 2-piperazin-1-ylethylamine | -1.48 | |
| 61788-44-1 | Phenol, styrenated | 4 | |

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

| CAS No. | Substance name | Results of PBT and vPvB assessment |
|------------|--|------------------------------------|
| 100-51-6 | benzyl alcohol | — |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | — |
| 1477-55-0 | 1,3-Benzenedimethanamine | — |
| 140-31-8 | 2-piperazin-1-ylethylamine | — |
| 84852-15-3 | Phenol, 4-nonyl-, branched | — |
| 61788-44-1 | Phenol, styrenated | — |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 10/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

12.6. Other adverse effects

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

| | |
|----------|--------------------------------|
| 08 02 99 | Wastes not otherwise specified |
|----------|--------------------------------|

Waste treatment options








Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Do not empty into drains.

SECTION 14: Transport information

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|--|--|---|--|
| 14.1. UN-No. | | | |
| UN 2735 | UN 2735 | UN 2735 | UN 2735 |
| 14.2. UN proper shipping name | | | |
| AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethana mine , nonylphenol) | AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethana mine , nonylphenol) | AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethana mine , nonylphenol , N-aminoethylpiperazine) | AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethana mine , nonylphenol) |
| 14.3. Transport hazard class(es) | | | |
|  8 |  8 |  8 |  8 |
| 14.4. Packing group | | | |
| III | III | III | III |
| 14.5. Environmental hazards | | | |
|  |  |  MARINE POLLUTANT | No |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 11/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|---|--|---|---|
| 14.6. Special precautions for user | | | |
| Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 80 Classification code: C7 tunnel restriction code: (E) Remark: | Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: C7 Remark: | Special provisions: 223 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-B Remark: | Special provisions: A3 Excepted Quantities (EQ): E1 Remark: |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Phenol, 4-nonyl-, branched. This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

15.1.2. National regulations

[DE] National regulations

Water hazard class (WGK)

WGK:

3 - stark wassergefährdend

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Mar 2020

Print date: 10 Mar 2020

Version: 2.1

Page 12/12

EUROTEAM
construction chemicals



EUROREPAIR PC 96 WHG Komponente B

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Acute toxicity (oral) (<i>Acute Tox. 4</i>) | H302: Harmful if swallowed. | |
| Skin corrosion/irritation (<i>Skin Corr. 1B</i>) | H314: Causes severe skin burns and eye damage. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Dam. 1</i>) | H318: Causes serious eye damage. | |
| Acute toxicity (inhalative) (<i>Acute Tox. 4</i>) | H332: Harmful if inhaled. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>) | H411: Toxic to aquatic life with long lasting effects. | |

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

| Hazard statements | |
|-------------------|--|
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H332 | Harmful if inhaled. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

16.6. Training advice

No data available

16.7. Additional information

No data available