

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 1/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROLASTIC Reiniger G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Product Categories [PC]

PC 35: Washing and cleaning products

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1

15345 Altlandsberg

Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Acute toxicity (dermal) (<i>Acute Tox. 4</i>)	H312: Harmful in contact with skin.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (...)	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

EUROTEAM
construction chemicals



Page 2/12

EUROLASTIC Reiniger G

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS08
Health hazard



GHS07
Exclamation mark

Signal word: Danger

Hazard components for labelling:

xylene; ethylbenzene; butanone; 1-methoxypropan-2-ol

hazard statements for physical hazards

H225	Highly flammable liquid and vapour.
------	-------------------------------------

hazard statements for health hazards

H304	May be fatal if swallowed and enters airways.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure. (...)

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements Response

P301 + P310.2	IF SWALLOWED: Immediately call a doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310.2	Immediately call a doctor.
P331	Do NOT induce vomiting.

Additional information:

Regulation (EC) No. 648/2004 (Detergents regulation): aromatic hydrocarbons Concentration: $\geq 30\%$

2.3. Other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 3/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CL P]	Concentration
CAS No.: 1330-20-7 EC No.: 215-535-7	xylene STOT SE 3, Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT RE 2, Asp. Tox. 1 Danger H226-H304-H312 + H332-H315-H319-H335-H373	> 50 Wt %
CAS No.: 100-41-4 EC No.: 202-849-4 REACH No.: 01-2119489370-35-XXXX	ethylbenzene Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1 Danger H225-H304-H332-H373	≥ 20 - < 30 Wt %
CAS No.: 78-93-3 EC No.: 201-159-0 REACH No.: 01-2119457290-43-XXXX	butanone STOT SE 3, Flam. Liq. 2, Eye Irrit. 2 Danger H225-H319-H336-EUH066	≥ 10 - < 20 Wt %
CAS No.: 107-98-2 EC No.: 203-539-1 REACH No.: 01-2119457435-35-XXXX	1-methoxypropan-2-ol STOT SE 3, Flam. Liq. 3 Warning H226-H336	≥ 2.5 - < 10 Wt %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing.

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. IF SWALLOWED: Call a doctor if you feel unwell. Aspiration hazard!

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. Drowsiness, Unconsciousness, Respiratory complaints, Depression of central nervous system, Headache, Dizziness, Nausea, IF SWALLOWED: Aspiration hazard. Subsequent observance for pneumonia and lung oedema. The product is skin resorptive. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 4/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Dry extinguishing powder, Carbon dioxide (CO₂), Water spray

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquid. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Use water spray jet to protect personnel and to cool endangered containers. Danger of bursting container. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

5.4. Additional information

No data available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up:

Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4. Reference to other sections

Personal protection equipment: see section 8, Disposal: see section 13, Dept. responsible for information: SECTION 1: Identification of the substance/mixture and of the company/undertaking

6.5. Additional information

No data available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Keep container tightly closed. Provide adequate ventilation as well as local exhaust at critical locations. Avoid contact with skin. Avoid contact with eyes.

Fire prevent measures:

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Combustible liquid. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 5/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

Advices on general occupational hygiene

Remove contaminated, saturated clothing immediately. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Keep away from food, drink and animal feedingstuffs. When using do not eat, drink or smoke. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on storage assembly:

Incompatible materials: Oxidising agent, Acid

Storage class: 3 - Flammable liquids

Further information on storage conditions:

Protect against: Heat. Protect against direct sunlight.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	xylene CAS No.: 1330-20-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
TRGS 900 (DE)	xylene CAS No.: 1330-20-7	① 100 ppm (440 mg/m ³) ② 200 ppm (880 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
TRGS 900 (DE)	ethylbenzene CAS No.: 100-41-4	① 20 ppm (88 mg/m ³) ② 40 ppm (176 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
IOELV (EU)	ethylbenzene CAS No.: 100-41-4	① 100 ppm (442 mg/m ³) ② 200 ppm (884 mg/m ³) ⑤ (may be absorbed through the skin)
IOELV (EU)	butanone CAS No.: 78-93-3	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
TRGS 900 (DE)	butanone CAS No.: 78-93-3	① 200 ppm (600 mg/m ³) ② 200 ppm (600 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
TRGS 900 (DE)	1-methoxypropan-2-ol CAS No.: 107-98-2	① 100 ppm (370 mg/m ³) ② 200 ppm (740 mg/m ³)
IOELV (EU)	1-methoxypropan-2-ol CAS No.: 107-98-2	① 100 ppm (375 mg/m ³) ② 150 ppm (568 mg/m ³) ⑤ (may be absorbed through the skin)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 6/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① parameter ② Test material ③ Time of sampling ④ Remark
TRGS 903 (DE)	xylene CAS No.: 1330-20-7	2,000 mg/L	① Methylhippur-(Tolur-)säure ② Urin ③ Expositionsende bzw. Schichtende
TRGS 903 (DE)	ethylbenzene CAS No.: 100-41-4	250 mg/g Creatinin	① Mandelsäure + Phenylglyoxylsäure ② Urin ③ Expositionsende bzw. Schichtende
TRGS 903 (DE)	butanone CAS No.: 78-93-3	2 mg/L	① 2-Butanon ② Urin ③ Expositionsende bzw. Schichtende
TRGS 903 (DE)	1-methoxypropan-2-ol CAS No.: 107-98-2	15 mg/L	① Methoxypropanol-2 ② Urin ③ Expositionsende bzw. Schichtende

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
xylene CAS No.: 1330-20-7	289 mg/m ³	① DNEL worker ② DNEL acute inhalative (systemic)
xylene CAS No.: 1330-20-7	174 mg/m ³	① DNEL Consumer ② DNEL acute inhalative (systemic)
xylene CAS No.: 1330-20-7	289 mg/m ³	① DNEL worker ② DNEL acute inhalative (local)
xylene CAS No.: 1330-20-7	174 mg/m ³	① DNEL Consumer ② DNEL acute inhalative (local)
xylene CAS No.: 1330-20-7	77 mg/m ³	① DNEL worker ② DNEL long-term inhalative (systemic)
xylene CAS No.: 1330-20-7	14.8 mg/m ³	① DNEL Consumer ② DNEL long-term inhalative (local)
xylene CAS No.: 1330-20-7	180 mg/kg bw/day	① DNEL worker ② DNEL long-term dermal (systemic)
xylene CAS No.: 1330-20-7	108 mg/kg bw/day	① DNEL Consumer ② DNEL long-term dermal (systemic)

Substance name	PNEC Value	① PNEC type
xylene CAS No.: 1330-20-7	0.327 mg/l	① PNEC aquatic, freshwater
xylene CAS No.: 1330-20-7	0.327 mg/l	① PNEC aquatic, marine water
xylene CAS No.: 1330-20-7	0.327 mg/l	① PNEC aquatic, intermittent release
xylene CAS No.: 1330-20-7	6.58 mg/l	① PNEC sewage treatment plant (STP)
xylene CAS No.: 1330-20-7	13.46 mg/kg	① PNEC sediment, freshwater
xylene CAS No.: 1330-20-7	12.46 mg/kg	① PNEC sediment, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 7/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary. Personal protection equipment: see section 8

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn. In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear protective gloves/protective clothing/eye protection/face protection.

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device with filter or ventilator filtering device of type: A

8.2.3. Environmental exposure controls

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

8.3. Additional information

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: colourless

Odour: characteristic

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	80 - 145 °C			
Decomposition temperature (°C):	<i>not determined</i>			
Flash point	7 °C			
Evaporation rate	<i>not determined</i>			
Ignition temperature in °C	<i>not determined</i>			
Upper/lower flammability or explosive limits	1 - 13.7 Vol-%			
Vapour pressure	9 hPa	20 °C		
Vapour density	<i>not determined</i>			
Relative density	0.86 g/cm ³	20 °C		
Bulk density	<i>not determined</i>			
Water solubility	Immiscible			
Partition coefficient: n-octanol/water	<i>not determined</i>			
Dynamic viscosity	<i>not determined</i>			
Kinematic viscosity	<i>not determined</i>			
Auto-ignition temperature	430 °C			
VOC	100 %			

9.2. Other information

In use may form flammable/explosive vapour-air mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 8/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air. May form explosive peroxides.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against direct sunlight.

10.5. Incompatible materials

Oxidising agent, strong; Acid;

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
1330-20-7	xylene	LD₅₀ oral: >2,000 mg/kg (Rat)
100-41-4	ethylbenzene	LD₅₀ oral: 3,500 mg/kg (Rat) LD₅₀ dermal: 15,400 mg/kg (Rabbit) ATE inhalativ Gase: 11 ppmV
107-98-2	1-methoxypropan-2-ol	LD₅₀ oral: 4,016 mg/kg (Rat)
78-93-3	butanone	LD₅₀ oral: >2,193 mg/kg (Rat)

Acute oral toxicity:

No information available.

Acute dermal toxicity:

1375 mg/kg

Acute inhalation toxicity:

Acute inhalation toxicity (vapour): 13,75 mg/l Exposure time: 4 h

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

No information available.

Germ cell mutagenicity:

No indications of human germ cell mutagenicity exist.

Carcinogenicity:

No indication of human carcinogenicity.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 9/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
1330-20-7	xylene	LC₅₀ : 2.6 mg/l 4 d (Oncorhynchus mykiss (Rainbow trout)) IC₅₀ : 1 mg/l (Daphnia magna (Big water flea)) EC₅₀ : 2.2 mg/l 3 d (Pseudokirchneriella subcapitata) NOEC : 0.44 mg/l 3 d (Pseudokirchneriella subcapitata)
100-41-4	ethylbenzene	LC₅₀ : 3.72 mg/l 4 d LC₅₀ : 8.78 mg/l 2 d EC₅₀ : 2.93 mg/l 2 d EC₅₀ : 4.6 mg/l 3 d EC₅₀ : 3.6 mg/l 4 d
107-98-2	1-methoxypropan-2-ol	LC₅₀ : 6,812 mg/l 4 d (Leuciscus idus (golden orfe)) DIN 38412 LC₅₀ : 20,800 mg/l 4 d (Pimephales promelas (fat head minnow)) LC₅₀ : ≥1,000 mg/l 4 d (Oncorhynchus mykiss (Rainbow trout)) OECD 203 LC₅₀ : 21,100 - 25,900 mg/l 2 d (Daphnia magna (Big water flea)) ErC₅₀ : >1,000 mg/l (Pseudokirchneriella subcapitata) IC₅₀ : 1,000 mg/l (Activated sludge) OECD 209
78-93-3	butanone	LC₅₀ : 2,993 mg/l 4 d (Pimephales promelas (fat head minnow)) OECD 203 EC₅₀ : 308 mg/l 2 d (Daphnia magna (Big water flea)) OECD 202 EC₅₀ : 1,972 mg/l 3 d (Pseudokirchneriella subcapitata) OECD 201

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	Remark
107-98-2	1-methoxypropan-2-ol	Yes, rapidly	insoluble in: Water
78-93-3	butanone	Yes, rapidly	Water solubility (g/L):partially soluble

12.3. Bioaccumulative potential

CAS No.	Substance name	Log K _{OC}	Bioconcentration factor (BCF)
100-41-4	ethylbenzene	3.15	
107-98-2	1-methoxypropan-2-ol	0.37	
78-93-3	butanone	0.3	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
1330-20-7	xylene	—
100-41-4	ethylbenzene	—
107-98-2	1-methoxypropan-2-ol	—
78-93-3	butanone	—

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 10/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Consult the appropriate local waste disposal expert about waste disposal.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

Remark:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation.





Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

No data available

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN-No.			
UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name			
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
No	No	No	No

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 11/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.6. Special precautions for user			
Special provisions: 274 601 640D Limited quantity (LQ): 1 L Hazard identification number (Kemler No.): 33 Classification code: F1 tunnel restriction code: (D/E) Remark:	Special provisions: 274 601 640D Limited quantity (LQ): 1 L Classification code: F1 Remark:	Special provisions: 274 Limited quantity (LQ): 1 L EmS-No.: F-E, S-E Remark:	Special provisions: A3 Remark:

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Only use containers specifically approved for the substance/product.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

 [DE] National regulations

Restrictions of occupation

22 JArbSchG. 5 MuSchRiV. 4 MuSchRiV.

Störfallverordnung

for substances contained in the product:

Störfallverordnung: Yes. P7 Pyrophoric liquids and solids

Water hazard class (WGK)

WGK:

2 - deutlich wassergefährdend

Description:

Classification according to VwVwS, Annex 4.

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

15.3. Additional information

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30-Jun-2016

Print date: 29-Aug-2018

Version: 5.0

Page 12/12

EUROTEAM
construction chemicals



EUROLASTIC Reiniger G

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Acute toxicity (dermal) (<i>Acute Tox. 4</i>)	H312: Harmful in contact with skin.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (...)	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure. (...)
H373	May cause damage to organs through prolonged or repeated exposure. (ears)

Supplemental Hazard information (EU)	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.