



EUROTEAM

EUROLASTIC Primer B 1

Moisture-curing 1-component primer

PRODUCT DESCRIPTION	EUROLASTIC Primer B 1 is a 1-component primer for absorbent substrates.
SCOPE	<ul style="list-style-type: none">- Primer for pretreating the joint edges and bonding surfaces- Ensuring the adhesion of sealants and adhesives to absorbent substrates- Absorbent substrates can include: e.g. concrete, aerated concrete, stone, plaster, wood (see primer matrix)
PRODUCT FEATURES	<ul style="list-style-type: none">- single component- low viscosity
COLORS	transparent, fluorescent
SUBSTRATE PREPARATION	The substrate must be dust-free, firm, dry and load bearing, free from loose and friable parts as well as separating substances such as oil, grease, paint residues or similar.
BACKFILL	The backer rod must be installed before the primer is applied.
PROCESSING CONDITIONS	Processing temperature: between +10°C and +35°C. The dew point must be taken into account! (+3 °C above dew point) For unknown or new materials, suitability and compatibility testing is essential.
PROCESSING	Apply the sealant or adhesive evenly and not too thickly with a brush before applying it. The minimum- Drying time is approximately 5 minutes.
CLEANING	The tools can be cleaned with EUROLASTIC Cleaner G from Fresh material can be cleaned. Once reacted, it can only be cleaned mechanically.



EUROTEAM

CONSUMPTION	80 - 100 g/m ² The consumption figure is a guideline. It can be significantly higher on very uneven/rough surfaces.
PACKAGING	EUROLASTIC Primer B 1 It is supplied in 1L containers.
STORAGE AND SHELF LIFE	Store in cool and dry conditions (not below +10°C). Under these conditions, the shelf life in the unopened and undamaged original container is 6 months.
GISCODE	Germany: Hazardous Substance Information System of the German Social Accident Insurance Institutions for the Construction Industry: GISCODE PU50
SPECIAL INSTRUCTIONS/PROTECTIVE MEASURES	EUROLASTIC Primer B 1 should only be applied in well-ventilated areas. Waste and containers must be disposed of safely. Avoid release to the environment. The instructions in the corresponding safety data sheet must be strictly observed. Avoid contact with eyes and skin. Wear impermeable protective gloves and safety goggles. Do not eat, smoke, or use open flames during processing. Do not inhale vapors! In confined spaces, wear a respirator with a filter for organic solvents. Completely empty containers can be returned to the KBS/Interseroh recycling system. Information on specific hazards and safety advice can be found in the safety data sheets. Processing equipment and any soiling can be cleaned with a suitable solvent before the primer has cured.
HAZARD WARNINGS	Hazard class A1 (Flash point below +21 °C)



EUROTEAM

TECHNICAL DATA *

TECHNICAL SPECIFICATIONS	UNIT	VALUE
Material basis		Synthetic resin, solvent-based
Number of components		1-component
Density at +23°C (DIN 53479)	g/cm ³	approximately 0.91
Relative humidity	%	min. 50 max. 85
Open time	h	8
Object and processing temperature	°C	from +10 to +35
Flash-off time at +23°C/50% r.l.h.	min	at least 5

*These figures are guidelines only. They are not intended for creating specifications.

The data were obtained at +23°C and 50% relative humidity. Higher temperatures and/or higher relative humidity may shorten or lengthen these times. All technical data, dimensions, and information in this datasheet are based on laboratory tests. Actual measured data may differ in practice.

May 2026 / Technical changes and further developments are reserved. Any liability arising from advertising materials is excluded. Advice of any kind, including regarding any third-party intellectual property rights, is provided for informational purposes only and is non-binding. The customer is solely responsible for the suitability of the goods for their intended purpose. All orders are subject to the seller's/manufacturer's terms and conditions of sale. or the production of goods. Reprinting is not permitted.